

TRAILER SPECIFICATIONS FOR: COMMERCIAL MODEL 20' JUSTICE

GVW Rating:	7,000#
Net Carrying Capacity:	6,000#
Coupler:	Surge type. 7500# gross load.750# tongue weight. 2 5/16" ball size.
Axles:	2 each, Hot Dip Galvanized 6000# Dura-Flex Rubber Torsion Axles. Galvanized Torsion Arm and Galvanized Inner Metal
Jack:	5000# Sidewind Bulldog Drop Leg Jack
Hubs:	6 bolt, 5 1/2" bolt circle. 3000# cap. ea. w/Safety Lube lubrication system
Wheel & Tire Assy:	Galvanized 14" wheel w/ST205/75R14 Radial trailer tire. 1760# cap @ 50 psi
Brake System:	10" DEEMAXX Hydraulic surge disc type. CAD Brakes. All Brake line #316 stainless steel.
Winch & Winch Stand:	2600# capacity, 2 speed, plated. Mounted on all Aluminum Winch Stand.
Winch Strap or Cable:	5/16" galvanized aircraft cable w/hook or 2" Yellow Strap w/hook.
Light & Wiring System:	Two LED submersible 8 function tail Lights. Four all plastic casing non- corrosive side marker lights. All plastic casing non-corrosive 16 gauge double insulated marine wire right & left side operating independently of each other. 5-way vehicle connector
CutWater Rollers:	Stoltz polyurethane rollers. Aluminum brackets with SS Fastners. Carpeted V Assy w/Polymar
Bunks:	Carpeted. Pressure treated wood, through Bolted to I'Beam with 3/8 stainless steel bolts.
Fenders:	Diamond Plate Aluminum .125 Structurally mounted to support 300# Live load.
Frame:	6.5" x 4" 6061 T6 Aluminum I Beam
Cross Members:	4" x 2 3/4" 6061 T6 Aluminum Channel
Fasteners:	All 18-8 Stainless Steel w/nylon lock nuts & washers
Guides:	PVC covered. Schedule 40 Aluminum Pipe double wall w/Stainless Steel U Bolts